



# PRODUCT BULLETIN



## Orange Dual Wall, Adhesive-Lined Heat Shrink – To Service the EV Market

### Orange Colour Available in Two Sizes – 1/2" and 3/4"

- 3:1 shrink ratio
- Made of adhesive-lined, cross-linked polyolefin that is flexible and easy to work with
- Adhesive inner wall provides superior sealing against water, moisture and other contaminants
- Excellent for coverage of irregularly shaped connectors and components
- Will bond to plastics, rubber, neoprene, steel and polyethylene
- Provides added strain relief and sealing of terminals and connectors
- Electrical insulation of simple in-line splices
- Abrasion-resistant for tubes and pipes
- Can also be used to repair damaged wire harnesses
- Operating temperature: -55°C to +125°C
- Minimum shrink temperature: 120°C
- Flame retardant

#### Dual Wall, Adhesive/Lined Heat Shrink Tubing – Orange

Expanded ID (Trade Size)	Recovered/Shrunk ID (Approx)	Use with Wire Size (Approx)	Length	Colour	Pkg Qty	Pkg Type	Part#
1/2"	3/16"	8-2GA	4FT	Orange	25 pcs	Box	*769784B
3/4"	1/4"	4-2/0GA	4FT	Orange	10 pcs	Box	*769785B



Dual Wall, Adhesive/Lined Heat Shrink Tubing – 4FT Lengths